

WATERFORD™

Sand Systems

by Sta-Rite®



Maximum capacity, minimum maintenance and cost

Add sparkle to your aboveground pool and spend less time maintaining it. Sand media is a long-established method of pool water filtration and Sta-Rite raised the bar on performance with its Waterford™ sand system.

- Great performance and efficiency. The 8-spoke filter hub evenly distributes water through the entire sand layer, which increases dirt-holding capacity. And because the spoke laterals are installed in the “slots down” position, sand will never find its way to your pool.
- Innovative filter design maximizes use of the filter’s surface area to trap more dirt and reduce cleaning frequencies.
- Ideal for aboveground pools up to 26,000 gallons.



For quick cleaning, simply move the valve lever to the backwash position—that’s it!

WATERFORD™ Sand System



- Easy-to-read top-mounted pressure gauge.
- Multiport valve selector activates backwashing action with one quick turn.
- One-piece polyethylene tank will never corrode.
- Pump options—available with ½ through 1½ HP pumps.

The low cost, easy-to-maintain filter system

Waterford™ sand systems offer a variety of pump and filter combinations that allow you to precision-match your system to almost any pool requirement. Everything is easily assembled on a compact, heavy-duty platform. And nothing could be easier to operate or maintain—a simple twist of the wrist puts the Waterford filter system in backwash mode for quiet, efficient cleaning action.

Economical

The sand filtration media is permanent—no need to replace cartridge-style elements.

Built to last

The Waterford filter tank and internal components are constructed of heavy-duty polyethylene, and the pump is made of Sta-Rite's exclusive Dura-Glas™ composite resin. This system won't corrode and resists the elements for years of service.

Filter Performance

Model	For Pools up to (Gal.) 8 Hr. Turnover	Filter Area (Sq. Ft.)	Pump ¹ (HP)	Sand Required ² (lbs.)
JSAL15C	12,000	1.2	½	100
JSAL15D	14,000	1.2	¾	100
JSAL15E	15,000	1.2	1	100
JSAL180D	18,000	1.8	¾	150
JSAL180E	20,000	1.8	1	150
JSAL210E	23,000	2.2	1	200
JSAL210F	26,000	2.2	1½	200

¹Available with ABG or JWP Series aboveground pumps.

²Use only #20 white quartz silica sand, size range .40–.55mm; 12"–15" sand bed depth required.

Operating Limits - Maximum continual operating pressure of 30 PSI. Pool applications maximum operating water temperature (internal filter) 95°F (35°C).

NOT RECOMMENDED FOR SPA APPLICATIONS

One-year limited warranty. See warranty for details.

Available from:



Simply Smarter.

www.staritepool.com

Phone: 800-831-7133 Fax: 800-284-4151



pumps / filters / heaters / heat pumps / automation / lighting / cleaners / sanitizers / maintenance products