

PRECAUTIONARY STATEMENTS

DANGER. CORROSIVE TO EYES AND SKIN. Causes eye irritation. Avoid contact with eyes or skin. Wear rubber gloves and safety glasses or goggles when handling. Not for internal use.

DIRECTIONS FOR USE

Metal Out is best used for prevention of metallic stains and hard water scaling. It sequesters (picks up) the material causing stains and scale and holds them in solution. If stains exist, they may be old ones requiring complete cleaning of the walls, or stains of an organic nature. Dissolved metals and minerals (such as Iron, Calcium, Manganese, and Magnesium) in pool water and corrosion of metal pool fittings will often cause staining and/or scaling. Do not let pH of pool water fall below 7.0 or serious corrosion problems may result. For scale prevention it is also essential to maintain pH at 7.2 to 7.6, total alkalinity at 100 to 150 ppm, and calcium hardness at 100 to 275 ppm.

STAIN AND SCALE PREVENTIVE MAINTENANCE

1. Before using **Metal Out**, adjust pH between 7.2 to 7.6
2. For best results, use this product in the evening with pool pump and filter operating overnight.
3. Add 4 to 6 ounces per 10,000 gallons every 4 to 5 days by premixing into plastic pail of water first. Dispense solution at deep end of pool.
4. Cloudiness may develop with the appearance of white flakes. This is normal indicating **Metal Out** is working and cloudiness will eventually disappear.



Made in USA



METAL OUT 16 oz.

Distributed by:

Doheny Enterprises

6950 51st Street Kenosha WI 53144

The Doheny's name and logo are registered trademarks of Doheny Enterprises, Inc.

Rev no. 1011