PRECAUTIONARY STATEMENT

CAUTION, MILD SKIN AND EYE IRRITANT, HARMFUL IF SWALLOWED.

GENERAL INFORMATION

Extra-Strength Flocculent thoroughly settles suspended debris (carbonates, silica, dead algae and spore-like materials) to the pool bottom so debris maybe easily vacuumed to waste. Use with normal pH and Free Chlorine levels. This product contains no corrosive alum or chloramine forming ammonia, will not affect pH, and is safe for all pools and filters.

WATER WITH ALGAE OR SPORE-LIKE MATERIAL

- 1. Extra-Strength Flocculent will not kill algae or spores, but assists in their removal after being treated with chlorine. Double or triple shock pool with suitable chlorine shock such as a Calcium Hypochlorite shock or Lithum Hypochlorite shock in the evening.
- Let filter run two hours and turn off.
- 3. The following morning, follow steps 1 through 8 outlined below if "cloudy water" persists.

DIRECTIONS FOR USE

- 1. SHAKE WELL BEFORE USING.
- 2. For best results, adjust pool water pH to 8.0.
- 3. Use at a rate of 8 oz. per 10,000 gallons.
- 4. Add Extra-Strength Flocculent slowly into skimmer with pump on and filter valve in Recirculate or Whirlpool position. For filters without Recirculate position: backwash, with filter in Filter Mode, dilute Extra-Strength Flocculent into large plastic pail of water and apply evenly over surface of pool.
- 5. Let pump circulate water for 2 hours to distribute Extra-Strength Flocculent throughout pool.
- 6. Shut off pump. Let Extra-Strength Flocculent settle debris to bottom while pool remains undisturbed for 12 to 48 hours (usually, overnight.) Note: The greater the debris in the water, the faster this product works. To speed settling time, you may double or triple dosage.
- 7. VACUUM TO WASTE all settled debris with filter in Waste or Drain Mode. Note: Settling may continue for several days if new debris is introduced by wind or rain. If so, vacuum to waste again.
- 8. Backwash and clean filter and resume normal filter cycle.

